

**BONE STOCK MINI VAN/TRUCK SUV RULES**  
**For**  
**Golden Spike Derailer & Mini Madness filler heats**

- 1- This is a NEW class meant to be simple, safe, cheap and easy. DO NOT do any more than what is stated below.
- 2- ANY MINI VAN MINI TRUCK AND MINI SUV WITH A V6 OR SMALLER ENGINE MAY BE USED.
- 3- All vehicles must exhibit the ability to stop at any time, if your brakes don't work, you will not compete.
- 4- ALL garbage, glass, plastic, pot metal, wheel weights, and screws must be removed, including but not limited to, all outer hardware, door handles, lock cylinders, trim, moldings, screws and fiberglass. Nothing may remain in the bottom of the interior, doors, or trunk. All seats except driver seat and any flammable material must be removed from the entire car. All trailer hitches must be removed. This rule excludes safety padding for driver. Dash may stay in place.
- 5- NO STOCK FUEL TANKS ALLOWED, MUST BE REMOVED!!!! All cars must have a metal fuel cell mounted inside the car. EFI cars must use either OEM connections or double clamp all connections. Must use correct rated pressure fuel hose. Power switches for electric fuel pumps should be clearly marked and shown to officials. Safety is #1 priority here.
- 6- ALL DOORS, HOOD & TRUNK MUST BE WELDED SHUT WITH A TOTAL OF FOUR WELDS PER DOOR HOOD AND TRUNK USING A MAXIMUM SIZE OF 6" X 2" X ¼" PLATE. DRIVERS DOOR MAY BE FULLY WELDED.
- 7- NO aftermarket parts are allowed except for the fuel cell, battery box and front bumper.
- 8- No altering of the cars body, suspension, rear bumpers, motors or anything else other than the fuel cell, battery box, front bumper and seat belts and safety cage is allowed.
- 9- Tires must be stock tires and rims that came on that vehicle. Tires may be tubed with a valve stem protector only.
- 10- A safety bar behind the driver's seat from side to side is mandatory with a minimum of a 10" x 10" end plate on each side of the bar
- 11- A driver & passenger door bar on the exterior of the door is mandatory. It must be a minimum of 10" wide and may go no further than 6" past the door seam. You may have one on the passenger door if you want to
- 12- A halo or upright bar attached to the rear seat bar is mandatory and must be fastened to the Roof.
- 13- No cage material may be attached to the floor.
- 14- You may use a non-loaded factory passenger car bumper or 4"x 4" x ¼" open ended square tube on the front of the car only.
  - a. It must be no wider than the center of front tires.
  - b. May only be mounted to the existing frame rail/unibody. You may use no more than a 6" x 6" x ¼" plate to accomplish this.
  - c. No bumper straps allowed.
  - d. Front frame rails may be only be trimmed enough to mount the front bumper.

