

## CROWN VIC

Entry level way to enter stock car racing

Keep the car stock

## BODY

- A. Front and Rear Bumper must remain stock with NO sharp edges. Bumpers must have tow chains front and rear
- C. Hood and trunk may utilize stock hinges but must be secured with hood pins.
- D. No hulling or lightening of body. The only areas on car that may be hulled are the front driver and passenger doors.
- E. All flammable materials and glass must be removed.
- F. Any holes in front firewall and rear firewall must be covered with aluminum or steel.
- G. All cars must have numbers on front doors and roof.
- H. Steering column must remain stock, all airbags must be removed.
- I. Must have at least (4) vertical windshield bars in front of driver.
- J. Roll cage must be inside driver compartment only, NO part of cage may extend outside of driver compartment.
- K. Four (4) driver door bars and three (3) passage door bars minimum.
- L. Cage must be securely mounted to FRAME

## SUSPENSION

- A. No altering of stock suspension.
- B. Stock adjustments only on modification

## ENGINE/TRANSMISSION

- A. Engine must be completely stock.

- B. 4.6 SOHC
- C. Exhaust must exit behind driver.
- D. Catalytic converter may be removed.
- E. Transmission must be completely stock.
- F. A.C. condenser must be removed.

#### SAFTY

- A. Drivers must wear fire suit, racing gloves, racing shoes and helmet while on track.
- B. Hans device recommended.
- C. Racing seat and belts mandatory.
- D. Racing belt must have five (5) point system.
- E. Fire extinguisher required in all cars.

#### TIRES/WHEELS

- A. Tires must be DOT legal, and all four (4) tires must be the same size.
- B. Wheels must be stock steel and all four (4) wheels must be same size and offset.
- C. No wheel spacers of any kind.
- D. Tire size 235/55/17 225/60/16. 215/70/15 All season tires only

#### WEIGHT

- A. No weight can be added

#### REAR-END

- A. Must be factory stock rear-end with stock components.
- B. The only legal gears will be 2.73, 3.27 and 3.55
- C. Rear differential may be locked by welding spider gears or stock limited slip carrier only but gear ratio rule remains the same (3.55 max gear)

#### FUEL

A. Pump gas only! NO RACING FUEL!

B. Stock fuel tank and fuel pump only.

THE ABSENCE OF A SPECIFIC RULE DOES NOT IMPLY APPROVAL, CONSENT OR PERMISSION REGARDING THAT SUBJECT. ANY QUESTIONS OR DOUBTS SUCH MATTERS SHOULD BE DIRECTED TO RACETRACK OFFICIALS FOR A CLARIFICATION.